

DV DA 20 KATANA

80 HP

POWER SETTING

PAlt	55%			65%			75%			85%		
	RPM	MP	L/h	RPM	MP	L/h	RPM	MP	L/h	RPM	MP	L/h
SL	2000	24,7	11,3	2100	25,7	13,0	2200	27,0	15,0	2400	27,7	18,3
2000	2000	24,0	12,0	2100	24,7	13,3	2300	25,7	15,3	2400	26,7	18,7
4000	2000	23,3	13,0	2200	23,3	14,0	2400	24,3	16,3	2400	25,7	21,0
6000	2100	22,0	14,0	2300	22,7	16,3	2400	23,3	19,3			
8000	2200	21,0	15,0	2300	21,7	17,7	2400	22,0	19,7			
10000	2300	19,7	16,0	2400	20,3	18,7						
12000	2400	18,0	17,3									

Angaben gültig für Standardatmosphäre (ISA)

DV DA 20 KATANA

100 HP

POWER SETTING

PAlt	55%			65%			75%			85%		
	RPM	MP	L/h	RPM	MP	L/h	RPM	MP	L/h	RPM	MP	L/h
SL	1900	24,7	13,6	2000	25,7	15,6	2100	27,0	18,0	2260	27,7	22,0
2000	1900	24,0	14,4	2000	24,7	16,0	2200	25,7	18,4	2260	26,7	22,4
4000	1900	23,3	15,6	2100	23,3	16,8	2260	24,3	19,6	2260	25,7	25,2
6000	2000	22,0	16,8	2200	22,7	19,6	2260	23,3	23,2			
8000	2100	21,0	18,0	2200	21,7	21,2	2260	22,0	23,6			
10000	2200	19,7	19,2	2260	20,3	22,4						
12000	2260	18,0	20,4									

Angaben gültig für Standardatmosphäre (ISA)